

Module 36

Oxygen (O2) Sensor Monitor

Author: Grant Swaim

E-mail: sureseal@nr.infi.net

URL: www.tech2tech.net

Phone: (336) 632-9882

Fax: (336) 632-9688

Postal Address: Tech-2-Tech Website
PO Box 18443
Greensboro, NC 27419

Physical Address: 220-4 Swing Rd
Greensboro, NC 27409

Last Update: April 2000

IMPORTANT - READ !

Do not read or study this information unless you agree to the following conditions:

The information in this training module is the intellectual property of N. Grant Swaim and is copyrighted by Sure Seal Products Inc.

Subscribers to the Tech-2-Tech website, and persons participating in Tech-2-Tech's on-line training program are entitled to read this material on-line.

You may also click on the "save" icon on the Acrobat viewer and save a copy to your local computer. You may save a copy of this file on one computer and it must be viewed from that one computer.

You may also print one copy of this file for your viewing. If the printed copy becomes illegible, or lost, an additional copy may be printed.

Tech-2-Tech offers the following training modules in printed manual, CD-ROM, and on-line formats.

PGMFI Training Modules

- The PGMFI System Overview—Part 1
- The PGMFI System Overview—Part 2
- PGMFI Flash Type DTCs
- Inputs / Outputs—Part 1
- Inputs / Outputs—Part 2
- Engine Control Module
- Air Flow / MAP Sensor—Base Inj Pulse Width
- Fuel Delivery System
- Closed Loop Strategies—Theory
- Closed Loop Strategies—Case Studies
- Thermistor Inputs
- Throttle Position Sensor
- EGR Valve Lift Sensor
- MAP / BARO Sensor
- Ignition Inputs
- Vehicle Speed Sensor
- Oxygen Sensor
- Lean Air Fuel Sensor
- Miscellaneous Input Signals
- Fuel Injectors—Multi-Port Injection
- Fuel Injectors—Dual Point Injection
- Ignition System—Outputs
- Idle Air Control Valve

OBD-II Training Modules

- On Board Diagnostics—General Overview
- Diagnostic Trouble Codes
- MIL / Freeze Frame
- Scan Tool
- Scan Tool—Advanced
- Monitor Tests—Overview
- Comprehensive Component Monitor
- Catalyst Monitor
- EGR Monitor
- Evaporative Monitor
- Fuel System Monitor
- Misfire Monitor
- Oxygen Sensor Monitor
- Oxygen Sensor Heater Monitor
- "P" Codes

Miscellaneous Training Material

- Glossary of Terms

36 Oxygen Sensor Monitor

Run:	Once-Per-Trip
Enable Criteria:	<ol style="list-style-type: none"> 1. Start the engine and allow it to warm up 2. Drive the vehicle at 40-55 mph for at least 2 minutes 3. Reduce the speed to 35 mph and maintain this speed until the monitor runs.
DTC	<p>A diagnostic trouble codes (DTC) generated from this monitor is stored on the first malfunction.</p> <p>All DTCs set from this monitor are standard priority within the freeze frame writing strategy. A freeze frame written by one of these DTCs can only be over written by a high priority DTC, not another standard priority DTC.</p>
MIL Info	<p>Illumination The malfunction indicator light (MIL) is illuminated when the first malfunction is recorded.</p> <p>Extinguishing The MIL is extinguished after three trips without a malfunction reoccurring.</p>
General Info:	

<i>DTCs Generated by the Oxygen Sensor Monitor</i>			
OBD Code	MIL Flash	Trips	Description
P0131	1	1	Primary HO2S Circuit - Low Voltage
P0132	1	1	Primary HO2S Circuit - High Voltage
P0133	61	2	Primary HO2S Circuit - Slow Response
P1149	61	?	Primary HO2S Circuit - Range / Performance
P1162	48	1	Primary HO2S Circuit - Malfunction
P1163	61	2	Primary HO2S Circuit - Slow Response
P1164	61	2	Primary HO2S Circuit - Range / Performance
P1165	61	2	Primary HO2S Circuit - Range / Performance
P1168	48	2	Primary HO2S LABEL - Low Input
P1169	48	2	Primary HO2S LABEL - High Input
P0137	63	1	Secondary HO2S Circuit - Low Voltage
P0138	63	1	Secondary HO2S Circuit - High Voltage
P0139	63	2	Secondary HO2S Circuit - Slow Response